

Full 3D

Optoma projectors can display true 3D content from almost any 3D source, including 3D Blu-ray players, 3D broadcasting and the latest generation games consoles. Support for 144Hz rapid refresh rate provides ultra-smooth flicker free images.

Eco AV Mute

Stay in control of your presentation with Eco AV mute. Direct your audience's attention away from the screen by blanking the image when no longer needed. This also reduces the power consumption by up to 70%, further prolonging the life of your lamp.

Auto Power Off

There may be instances when the projector is left running when not in use. To help save energy, the "Auto Power Off" feature automatically turns off the projector after a set period of time if it is not being used.

Control

Featuring a wide range of options you can remotely control and monitor the projector.

·RS232

Optoma projector's come with an extensive set of RS232 commands making it simple and easy to manage using any control system.

·AMX Compatibility

Dynamic discovery protocol is incorporated into the projector allowing for easy installation with AMX control systems.

MHL Connectivity

Turn your projector into a smart display by connecting your smartphone or tablet with a single cable using MHL; now you can view presentations and documents, stream videos and share photos on the big screen.

Integrated Speaker

The built-in 10W speaker offers excellent audio support. Easy to set up without the need for costly external speakers.

I/O Connections

01 RS232

02 VGA (YPbPr)

03 HDMI1/MHL

04 HDMI2

05 USB Power

06 Mouse/Service





Specification	EH341
Display Technology	Single 0.65" DarkChip 3 1080p DLP® Technology by Texas Instruments
Native Resolution	1080P (1920 x 1080)
Brightness / Contrast Ratio	3700 ANSI Lumens / 20,000 :1
Display Colors	1073.4 million colors (10bit)
Projection Lens	F/2.5~2.67; f=21.9~24mm, 1.1x Manual Zoom
Image Size	30~260"
Projection Distance	1.5~10m
Throw Ratio	1.48~1.62
Digital Keystone Correction	± 30° Vertical
Aspect Ratio	16:9 Native, 4:3 Compatible
Scan Rate	Horizontal : 15.375~91.146 KHz; Vertical : 24 ~ 85Hz (120Hz for 3D)
Computer Compatibility	UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
Video Compatibility	1080p, 1080i, 720p, 576i/p, 480i/p
Input / Output Connections	2 x HDMI (1.4a 3D support) + MHL v1.2, VGA (YPbPr), RS232, USB mouse/service, USB-A Power
Uniformity	80 %
Noise	29 dB
Lamp Life	6000 Hrs (Eco mode)
Power Supply	Universal AC 100 ~ 240V± 10%,50/60Hz
Dimensions (WxDxH) / Weight	315 x 224 x 102 mm / 2.55 kg

*Optoma reserves the right to change this brochure without prior notice, please refer to www.optoma.com for any change

